



NOTE: ALL FREEZER DOORS MUST HAVE SEPERATE 120 VOLT SUPPLY FOR HEATER CABLES FOR BOTH DOORS

DRAWING NOTES—PLEASE SPECIFY ALL AREAS MARKED OTHER

OPTION NUMBER	DESCRIPTION

DOOR NO.	QTY.	W.I.C.	H.I.C.	LOCK	SAFETY RELEASE	FINISH COVERING	GAGE	USE

HERCULES
Renowned, resilient doors. By Kingspan

INSTALLATION REQUIREMENTS

- THE FLOOR UNDER THE DOOR MUST BE LEVEL AND SMOOTH
- THE WALL BEHIND THE DOOR FRAME MUST BE SMOOTH AND IN A COMMON PLANE

DOOR PANEL AND FRAME

- DOOR THICKNESS
4" 6" (FREEZER ONLY)
- TEMPERATURES
WALL SIDE TRACKSIDE
= _____ °F = _____ °F
- SLIDE DIRECTION
LEFT
RIGHT
- PANEL AND FRAME CLADDING
WHITE STUCCO EMBOSSED GALV STEEL
MILL FINISH STUCCO EMBOSSED STEEL
STAINLESS STEEL
SANDSTONE STUCCO EMBOSSED GALV STEEL
WHITE STUCCO EMBOSSED ALUMINUM
MILL FINISH STUCCO EMBOSSED ALUMINUM
- JAMBS
JAMB DEPTH _____
HDPE CLAD IN SAME MATL AS DOOR
CHANNEL TRIM
OTHER

OPTIONS

- FREEZER DOOR
HEATER WIRE RUN AROUND PERIMETER OF DOOR LEAF AND IN BOTTOM OF DOOR
- INSIDE CASINGS
- HOOD
MATCHED TO FACE OF DOOR
OTHER
- KICKPLATES
TRACKSIDE WALLSIDE
HEIGHT: 18" 24" 36" 48" OTHER
ALUMINUM DIAMOND PLATE
18 GA. STAINLESS STEEL
16 GA. GALV. STEEL
OTHER
- VISION PANEL
12 3/4" x 12 3/4" INSULATED
12 3/4" x 12 3/4" HEATED
OTHER
- LOCKING DEVICE
TRACKSIDE WALLSIDE
WITH SAFETY RELEASE
WITH NO SAFETY RELEASE

MANUAL BI-PARTING SLIDING DOOR

SCALE: NONE		DRAWN BY
DATE:		
For:		Job No.
		DRAWING NUMBER