



DOOR NO.	QTY.	W.I.C.	H.I.C.	USE	SWING	FINISH COVERING	GAGE	HARDWARE FINISH	RETURN DEPTH

**INSTALLATION REQUIREMENTS**

- I. THE FLOOR UNDER THE DOOR MUST BE LEVEL AND SMOOTH
- II. THE WALL BEHIND THE DOOR FRAME MUST BE SMOOTH AND IN A COMMON PLANE

**DOOR PANEL AND FRAME**

1. DOOR THICKNESS  4" (FREEZER ONLY)  6"
2. TEMPERATURES WALL SIDE = \_\_\_\_\_ °F HINGESIDE = \_\_\_\_\_ °F
3. PANEL AND FRAME CLADDING
  - WHITE STUCCO EMBOSSED GALV STEEL
  - SANDSTONE STUCCO EMBOSSED GALV STEEL
  - MILL FINISH STUCCO EMBOSSED STEEL
  - STAINLESS STEEL
  - WHITE STUCCO EMBOSSED ALUMINUM
  - MILL FINISH STUCCO EMBOSSED ALUMINUM
4. JAMBS
  - JAMB DEPTH \_\_\_\_\_
  - HDPE CLAD IN SAME MATL AS DOOR
  - CHANNEL TRIM
  - OTHER \_\_\_\_\_

**OPTIONS**

5.  FREEZER DOOR HEATER WIRE RUN AROUND PERIMETER OF DOOR LEAF ON WALLSIDE
6.  INSIDE CASINGS
7.  HOOD  MATCHED TO FACE OF DOOR  OTHER \_\_\_\_\_
8.  KICKPLATES
  - WALLSIDE
  - HINGESIDE
  - HEIGHT  DURUM  1/2"  1/4"  1/8"  1/16"
  - ALUM.  BRASS  PLATE
  - 18 GA. STAINLESS STEEL
  - 16 GA. GALV. STEEL
  - OTHER \_\_\_\_\_
9.  VISION PANEL
  - 12" X 12" INSULATED
  - 12" X 12" HEATED
  - OTHER \_\_\_\_\_
10.  LOCKING DEVICE
  - WALLSIDE
  - TRACKSIDE
  - WITH POWER CUTOFF & SAFETY RELEASE
  - WITH POWER CUTOFF - NO RELEASE
11.  RADIO CONTROL
12.  PHOTOCELL
  - TO OPEN
  - AS SAFETY
13.  MOTION DETECTOR
  - TO OPEN
  - AS SAFETY
14.  LOOP DETECTOR
  - TO OPEN
  - AS SAFETY
15.  TIMER DELAY CLOSE

**ELECTRIC VERTICAL LIFT DOOR**

SCALE: NONE	DRAWN BY
DATE:	
FOT:	Job No.
	DRAWING NUMBER