



- INSTALLATION REQUIREMENTS**
- I. THE FLOOR UNDER THE DOOR MUST BE LEVEL AND SMOOTH
 - II. THE WALL BEHIND THE DOOR FRAME MUST BE SMOOTH AND IN A COMMON PLANE

DOOR PANEL AND FRAME

1. DOOR THICKNESS
 - 4" (FREEZER ONLY)
 - 6"
2. TEMPERATURES
 - WALL SIDE = _____ °F
 - HINGESIDE = _____ °F
3. PANEL AND FRAME CLADDING
 - WHITE STUCCO EMBOSSED GALV STEEL
 - SANDSTONE STUCCO EMBOSSED GALV STEEL
 - MILL FINISH STUCCO EMBOSSED STEEL
 - STAINLESS STEEL
 - WHITE STUCCO EMBOSSED ALUMINUM
 - MILL FINISH STUCCO EMBOSSED ALUMINUM
4. JAMBES
 - JAMB DEPTH _____
 - HDPE CLAD IN SAWE MATL AS DOOR
 - CHANNEL TRIM
 - OTHER _____

OPTIONS

5. FREEZER DOOR
 - HEATER WIRE RUN AROUND PERIMETER OF DOOR LEAF ON WALLSIDE
6. INSIDE CASINGS
7. DOOR
 - MATCHED TO FACE OF DOOR
 - OTHER _____
8. KICKPLATES
 - WALLSIDE
 - HINGESIDE: 24" 36" 48" OTHER _____
 - ALUMINUM DIAMOND PLATE
 - 16 GA GALV. STEEL
 - OTHER _____
9. DIVISION PANEL
 - INSULATED
 - 12" X 12" HEAVY
 - OTHER _____
10. LCKING DEVICE
 - WALLSIDE
 - TRACKSIDE
 - WITH SAFETY RELEASE
 - WITH NO RELEASE

DOOR NO.	QTY.	W.I.C.	H.I.C.	USE	SWING	FINISH COVERING	GAGE	HARDWARE FINISH	RETURN DEPTH



MANUAL VERTICAL LIFT DOOR

SCALE: NONE	DRAWN BY
DATE	JOB NO.
FOR:	DRAWING NUMBER